Lumii Miixslat Panel Specification Sheet

Product Name: Miixslat-Light Oak, Dark Oak, Walnut, Blackened	
Panel Composition: 5mm (recycled content) Miixfelt PET black backing & 12mm luxury MDF sl	at
Panel Dimensions : 2600mm (+/- 3mm) x 300mm (+/- 3mm)	
Slat Dimensions: Depth 12mm x 45mm (5 Slats per 300mm panel)	
Thickness: 17mm (+/-0.5mm)	
Weight: 12.5kg Per Panel	
Colours: Light Oak, Dark Oak, Walnut, Blackened.	
PET Melting Point: 250°C Max.	
SAA (NRC) for Substrate: Substrate 0.85 with 50mm Air Gap	
Fire retardant: EN 13501-1 Class B-s1, d0	

UK Processing & Fabrication Service



Lumii Miixslat Panel Specification Sheet

ENVIRONMENTAL
Miifelt PET is manufactured using a minimum of 75% post-consumer recycled content (PET plastic
bottles). MDF is FSC & PEFC Certified. 100% Recyclable & Made in Europe.
HAZARDS IDENTIFICATION
Non-hazardous and non-dangerous goods.
CHEMICAL ENTITY
Surface: Oak veneer offered in Light Oak, Dark Oak, Walnut, & Blackened.
Slat Substrate: FCS PEFC Certified MDF
Substrate: 5mm black Polyester Fiber from PET (Polyethylene Terephthalate)
Key Features
· Manufactured using a minimum of 75% post-consumer waste & recycled material.
· Limitless branding and design possibilities with in-house custom cutting.
· Excellent acoustic performance.
· 0% Formaldehyde binders, cruelty free.
· Non-toxic, non-irritant and non-allergenic.
· Stocked in the uk.
UK Processing & Fabrication Service

